



SECURE WIRELESS AGILE NETWORKS

RF Fingerprinting to Aid Cyber Security in Low Cost Wireless IoT Systems:

16th September 2021

DCMS/SPF event on 6G: Software Defined Radio and RF Sampling


Mark Beach, Academic PI

Manish Nair & Tommaso Cappello


Communications Systems & Networks Group
Smart Internet Lab

University of Bristol

swan-programme@bristol.ac.uk



Secure Wireless Agile Networks (SWAN)



Secure Wireless Agile Networks (SWAN)

- Joint industrial / academic research programme addressing creation of Secure Wireless Agile Networks (SWAN) that are *resilient to both cyber-attacks and accidental or induced failures*.
- Funded through 3rd Call for UKRI/EP SRC Prosperity Partnerships, £40 million government, industry and university investment “*to transform the way people live, work and travel*” [see press release](#)
 - SWAN, with a £6.1M 5 year research programme, is one of six projects funded and started 1st February 2020
 - Toshiba Europe, Roke Manor Research, GCHQ & University of Bristol “*bringing together a cadre of engineers from industry, government and academia with invaluable commercial insights and in-depth technical skills capable of delivering holistic solutions for a productive, healthy, resilient and connected nation*”

Secure Wireless Agile Networks (SWAN)

- Wireless networks that underpin much of modern life are increasingly vulnerable to cyber-attacks and other induced failures.
- SWAN aims to develop secure wireless networks that are resilient to these threats, protecting individuals, businesses and society.
- The Research Programme will:
 - Identify vulnerabilities in the RF interfaces;
 - Development of techniques to detect and mitigate against the effects of cyber-attacks;
 - Create enabling technology for truly Software Defined Radios following “Secure by Design” principles;
 - Creation of more resilient and secure systems.

SWAN's Research Challenges

RC1: Threat Synthesis and Assessment

- Vulnerabilities of wireless to RF cyber attacks have received little attention.
- For critical infrastructure, impact of denial of service and manipulation of data and control need to be understood, as well as understanding the mechanics of such an attack.

Threat	Definition
Spoofing	Pretending to be someone/something other than yourself
Tampering	Modifying something on disk/network/memory/etc.
Repudiation	Claiming not to be responsible for something
Information Disclosure	Providing information to someone unauthorised to access it
Denial of Service	Exhausting resources required to provide service
Elevation of Privilege	Allowing someone to do something they are not authorised to do



SWAN's Research Challenges

RC1: Threat Synthesis and Assessment

- Vulnerabilities of wireless to RF cyber attacks have received little attention.
- For critical infrastructure, impact of denial of service and manipulation of data and control need to be understood, as well as understanding the mechanics of such an attack.

RC2: RF Cyber Detection & Defence

- Power and cost-effective solutions required for large-scale monitoring of potential attacks.
- Resilient waveforms, robust protocols and enhancement spatial processing techniques are required to defend assets.

SWAN's first candidate RAN: LoRaWAN

- Fast adoption of LoRaWAN as a low power, long range wireless IoT technology thanks to the LoRa Alliance®
 - **156** LoRaWAN Network Operators in **171** Countries
 - Multiple use cases, including critical infrastructure



**Environment
monitoring**



**Parking
management**



**Safety and
security**



Street lighting



**Waste
management**




- A number of studies have shown that LoRaWAN may be susceptible to jamming attacks

- E. Aras, N. Small, G. S. Ramachandran, D. Stéphane, W. Joosen, D. Hughes, (2018), "Selective Jamming of LoRaWAN using Commodity Hardware," *MobiQuitous 2017*, Melbourne, VIC, Australia, November 7–10, 2017, pp. 363–372, <https://doi.org/10.1145/3144457.3144478>
- Trend Micro Technical Brief: The current state of LoRaWAN security: <https://documents.trendmicro.com/assets/pdf/The%20Current%20State%20of%20LoRaWAN%20Security.pdf>

SWAN's Research Challenges

RC3: Cyber Secure Radio Design

- Need for RF architectures which are more resilient to attack and facilitate the detection of an adversary.
- RF transceivers which can offer enhanced frequency agility and thus support dynamic spectrum access (DSA)



SWAN's Research Challenges

RC3: Cyber Secure Radio Design


- Need for RF architectures which are more resilient to attack and facilitate the detection of an adversary.
- RF transceivers which can offer enhanced frequency agility and thus support dynamic spectrum access (DSA)

RC4: Secure Dynamic Spectrum Access


- Understanding the vulnerabilities of sharing protocols is essential if DSA is to be secure
- Need for enhanced RF transceiver technology to support a change from fixed spectrum allocation.

See Simon Wilson, 1st Workshop on 6G: Technology Enablers for Spectrum & Power Efficiency Wireless Access, 26th May 2021 (hosted by Uni of Bristol)

SWAN's Test Beds






RF Penetration Testing:
Inc: IQ Capture







Clifton Campus LoRaWAN
AP & Sensor deployments

Over the Air LoRa waveforms




I/Q Data




- Constellation rotation due to CFO

Fingerprinting LoRa: Neural Network (NN) Clustering of Differential Constellation Trace Figures


SODAQ-A




SODAQ-B




SODAQ-C




SODAQ-D




SODAQ-E



ARB



Fingerprinting LoRa: NN Clustering of Differential Constellation




`IQData[st:end].*conj(IQData[st:end])`

$6 \times [1 \times 16270]^H$
High Dimensional
Input Matrix







$[6 \times 10]$
Input
Weight
Matrix

$[6 \times \{10 \times 1^H, \dots, 10 \times 1^H\}]^H$
 $= 6 \times [10 \times 10]$
Kohonen
(NN) Layer Matrix




Trace Figures:
2D Self-Organizing
Feature Map

$6 \times [10 \times 10]$
Low Dimensional Output Layer
Matrix: 2D SOFMs



Fingerprinting LoRa: Classification based on CNN



- Expected to be invariant to MAC ID Spoofing: due to multiple 2D SOFMs from multiple training epochs

SWAN Quarterly Newsletter

Issue 1 - Autumn 2020



Sign up to our Quarterly Newsletter to receive regular updates on the latest SWAN news and research activities:

<https://bit.ly/332RR5z>



13/09/2021





SECURE WIRELESS AGILE NETWORKS

swan-programme@bristol.ac.uk

www.swan-partnership.ac.uk

www.bris.ac.uk/smart | www.bris.ac.uk/csn

@PartnershipSWAN

@bristol_smart | @BristolCSN

linkedin.com/company/swan-prosperity-partnership

13/09/2021

